









Cuadro

Wall Light


A recessed wall collection that combines form and function for the most practical applications



Small		Large	
Measurements (mm)		Measurements (mm)	
Luminaire	Wallbox	Luminaire	Wallbox
			
90x90 ( 77x77)	80x80	235x90 ( 220x72)	226x76
Absolute Luminous Flux		Absolute Luminous Flux	
2W (24V DC) 60lm (at 3000K)		8W (24V DC) 363lm (at 3000K)	
Beam		Beam	
90° (F)		90° (F)	

Finishes

- UV Textured Black
- UV Textured White
- UV Textured Grey



General Specifications

Material	Powder Coated Aluminium, PVC Wallbox
IP	65
Wiring	Wired in Parallel
Warranty	3 Years

LED

Colour Temp	3000K, 4000K
CRI (Ra/R9)	80+ / >0
Efficacy	Up to 55lm/W
Colour Deviation	SDCM ≤ 3
Lifetime	>54,000h L70B10

Driver

- 24V DC Remote Non-Dimmable Driver (CV2)
- 24V DC Remote Phase-Cut Dimmable Driver (PC2)
- 24V DC Remote Tridonic one4all DALI Dimmable Driver (TD2)
- 24V DC Remote Tridonic basicDIM Dimmable Driver (TB2)



A minimalist architectural design with a wide light distribution

Install high on walls, fixed up as an alternative to traditional general lighting inside

Assists in creating safe pathways

Two sizes available for different light level requirements

Beam Options



Flood | 90° (F)