



# Echo

# Wall Light

A thin and functional vanity luminaire with excellent colour rendering

600	900
<b>Measurements (mm)</b>	<b>Measurements (mm)</b>
<b>Absolute Luminous Flux</b>	<b>Absolute Luminous Flux</b>
<b>12W (300mA)</b> 660lm (at 3000K) 670lm (at 4000K)	<b>20W (500mA)</b> 1165lm (at 3000K) 1175lm (at 4000K)
<b>Beam</b>	<b>Beam</b>
110° (F)	110° (F)

### Finishes

Textured Black	
Textured White	

### General Specifications

<b>Material</b>	Powder Coated Aluminium, Frosted Acrylic Diffuser
<b>IP</b>	65
<b>Warranty</b>	3 Years

### LED

<b>Colour Temp</b>	3000K, 4000K
<b>CRI (Ra/R9)</b>	90+ / >50
<b>Efficacy</b>	Up to 52lm/W
<b>Colour Deviation</b>	SDCM ≤ 3
<b>Lifetime</b>	>50,000h L70B10

### Driver

<b>240V Built-in Non-Dimmable Driver</b>
240V Remote Tridonic one4all DALI Driver (TD)
240V Remote Tridonic basicDIM Bluetooth Driver (TB)



Ideal for vanity applications and for highlighting feature artwork in galleries and museums

Excellent colour rendering with a CRI rating of 90+

Designed with a protruded diffuser to allow for a 110° beam angle – producing a practical light in all directions

Dot-free illumination

### Beam Options



Flood | 110° (F)

### Notes

Echo Wall Light requires 60mm (600) / 75mm (900) of clearance from the mounting surface.