Open or Diffused Cone Design

A perfect combination of design and functionality, the Europa Street Light is available in an open or diffused cone.

Flexibility in Application

Whether it is a public park, pedestrian road or a public square, the Europa Street Light has been developed to be suitable for a variety of applications.

Compact and Lightweight

High quality aluminium alloy housing allows maximum protection whilst still being light weight in street application.

Durability

This street light has been designed with a double brace structure, giving it excellent durability and strength.

Europa

STREET LIGHT SERIES

Available with a unique open cone or diffused cone design, the Europa Street Light Series represents a new era of public lighting. Rigorously tested for maximum brightness and durability - this street light is a feat in outstanding design and considered engineering.

- Select from either an open or diffused cone design
- Custom powder coated colours available upon request
- Luminaire poles available upon request

Diffused Cone
Measurements (mm)
509 / 450
Absolute Luminous Flux
30W 1825lm **40W** 2800lm **50W** 3665lm
Beam
120° (F)
Weight
6.40kg
Spigot Diameter
88mm

Open Cone
Measurements (mm)
605 / 450
Absolute Luminous Flux
30W 2805lm **40W** 3370lm **50W** 4250lm
Beam
120° (F)
Weight
7.75kg
Spigot Diameter
88mm

Finishes

UV Textured Black	
UV Textured Grey	

General Specifications

Material | Powder Coated Aluminium
IP | 65
IK | 08
Warranty | 5 Years

Driver

Power Factor | >0.90
240V Built-in Non-Dimmable Driver
Dimming | DALI Dim Optional

LED

Colour Temp | 2700K, 3000K, 4000K, 5000K, 6000K
CRI | 70+
Efficacy | Up to 94lm/w
Colour Deviation | SDCM≤3
Lifetime | 65,000h L70

Notes

*Optional NEMA 7 Pin Socket available. Please email **sales@unios.com** for more information.*

Photometrics

Open Cone	Diffused Cone
	
α = 120°	α = 120°

A	B	C	D	E	F
EURD	0030	TB	30	-	- Driver

Example: **EURD0030.TB30.F**
Refer to data sheet for available configurations.
Visit Product Toolbox at **unios.com/europa** to configure compatible Osram/Tridonic DALI drivers.

A	Product Family	B	Power	C	Finish	D	CCT	E	Beam	F	Driver (*DALI drivers can be configured via Product Toolbox*)
EURD	Europa Street Light (Diffused Cone)	**0030**	30W	TB	Textured Black	**27**	2700K	F	Flood	-	*Driver code not required – driver is integrated into luminaire*
EURO	Europa Street Light (Open Cone)	**0040**	40W	TG	Textured Grey	**30**	3000K				
		0050	50W			**40**	4000K				
						50	5000K				
						60	6000K				

INDUSTRIAL