



Exon


LINEAR LIGHT

The Exon Linear Light is a versatile, weather-proof luminaire fit for projects and conditions of any kind. Available in IK08 rating with the ability to be surface mounted or suspended, this linear light is built specifically for the requirements of industrial projects.

- IK08 rating makes the Exon the ideal luminaire for industrial applications
- Cable entry has been designed for 20mm diameter conduit

Small (600mm)	Large (1200mm)
Measurements (mm)	
 600 84	 1200 84
Absolute Luminous Flux	
20W (500mA) 2285lm (at 4000K)	40W (1000mA) 4705lm (at 4000K)
Beam 120° (F)	

Photometrics



$\alpha = 120^\circ$



Finishes

White/Silver

General Specifications

Material | Powder Coated Aluminium with Toughened Polycarbonate Diffuser
IP | 65
IK | 08
Warranty | 5 Years


LED

Colour Temp | 4000K
CRI | 80+
Efficacy | Up to 119lm/w
Colour Deviation | SDCM \leq 3
Lifetime | 57,000h L70

Driver

Power Factor | >0.90
 240V Built-in Non-Dimmable Driver
Dimming | DALI Dim Optional

Accessories



EXON2000
2000mm Suspension Kit
(Suitable for all Exon Series)

A	B	C	D	E	F
ER08	0600	MW	30	F	- Driver
Product Family: ER08 Exon R08 Linear Light					
Size: 600mm / 1200mm					
Finish: MW Matt White					
CCT: 40 4000K					
Beam: Flood					
Driver (DALI drivers can be configured via Product Toolbox): - Driver code not required - driver is integrated into luminaire					

Example: ER080600.MW30.F

Refer to data sheet for available configurations. Visit Product Toolbox at unios.com/exon to configure compatible Osram/Tridonic DALI drivers.

