



Above: Residential application  
Left: Toughened polycarbonate diffuser




## Kobalt

OUTDOOR LIGHT

The Kobalt Outdoor Light is perfectly suited for coastal areas with a design that is resistant to discolouring or corrosion. This surface mounted luminaire can be mounted on both walls and ceilings for alfresco, portico and pillar applications. The Kobalt Outdoor Light is integrated with four hex screws for improved vandal proof capabilities.

- Available in textured black, white or silver finishes
- UV treated diffuser prevents cracking and discolouration
- A versatile luminaire that delivers maximum light output in a durable body

### Measurements (mm)




### Absolute Luminous Flux

	3000K	4000K
14W (450mA)	990lm	1140lm

### Beam

110° (F)

### Photometrics



$\alpha = 110^\circ$  (F)



### Finishes

UV Textured Black	
UV Textured White	
UV Textured Silver	

### General Specifications

<b>Material</b>   UV Powder Coated Toughened Polycarbonate
<b>IP</b>   65
<b>IK</b>   10
<b>Warranty</b>   3 Years

### LED

<b>Colour Temp</b>   3000K, 4000K
<b>CRI</b>   80+
<b>Efficacy</b>   Up to 81lm/w
<b>Colour Deviation</b>   SDCM $\leq$ 3
<b>Lifetime</b>   70,000h L70

### Driver

<b>Power Factor</b>   >0.90
24OV Built-in Non-Dimmable Driver
<b>Dimming</b>   DALI Dim Optional

### Notes

DALI Driver must be remote.



A	KOBA	0014	TB	30	F	-	Driver	Standard Non-Dimmable Driver included
B	0014							
C	TB	TW	TS					
D	30	40						
E	F							
F								

Example: **KOBA0012.TB30.F**  
Refer to data sheet for available configurations.  
Visit Product Toolbox at [unios.com/kobalt](https://unios.com/kobalt) to configure compatible Osram/Tridonic DALI drivers.

