


LX R56

RECESSED LINEAR LIGHT

1) Mounting Options (specify via sidebar)

See diagram below for installation spacing required



Clip System

Spring System

2) Profile



Direct

3) Diffuser




Opal

4) Optional Connection Accessories (specify via sidebar)



15W 90° Connector
(Includes LEDs and power supply)

Measurements (mm)



Beam

120° (F) | Opal

Finishes

Textured Black
Textured White

Custom powder coated finishes available upon request

General Specifications

Material | Powder Coated Aluminium
Weight | 1.05kg/Metre
IP | 40, 54
UGR (Unified Glare Rating) | <22
Warranty | 5 Years


LED

Colour Temp | 2700K, 3000K, 4000K
CRI | 82+
Efficacy | Up to 94lm/w
Colour Deviation | SDCM≤3
Lifetime | 60,000h L80B10

Driver

Power Factor | >0.90
240V Remote Non-Dimmable Driver
Dimmable remote driver option available
Dimming | 1-10V Dim (AD)
DALI Dim Optional

Photometrics



$\alpha = 120^\circ$ (Opal)



All absolute luminous flux listed at 4000K

Please email sales@unios.com or call +61 8 9248 1888 for custom lengths and wattages to suit projects.



Above: Office application
Right: Spring mounting system



F Driver (DALI drivers can be configured via Product Toolbox)
- Non-dimmable driver is integrated into luminaire - no code is required. For analogue or DALI options please specify via Product Toolbox

E Beam
F Flood

D CCT
27 2700K
30 3000K
40 4000K

C Finish
TB Textured Black
TW Textured White

B Size/Length
5605 1983mm
5608 2263mm
5611 1423mm
5614 1703mm
5617 1703mm

A Product Family
LXRS LX R56 (Recessed Direct w/Spring Mounting)
LXRC LX R56 (Recessed Direct w/Clip Mounting)

F Example: LXRC5605.TB30.W
Refer to data sheet for available configurations. Visit Product Toolbox at unios.com/lxr56 to configure compatible Osram/Tridonic DALI drivers.

A B C D E F
LXRC 5605 TB 30 W

224 unios Edition 28.6.18 | Product design and technical data may be subject to change

universal light | unios.com/lxr56

225