



Above: Residential application
Left: Wall application

Minq

WALL LIGHT

Whether installed indoors or outdoors, the Minq Wall Light bathes any wall in a luminous horizontal or vertical wash. This elegant luminaire emits light in both directions, providing many possibilities in application.

- Designed with a gently rounded shape
- Ability to be installed in a horizontal or vertical configuration
- Designed with strategically placed LEDs for maximum visual comfort

Measurements (mm)




Absolute Luminous Flux

4W (350mA)
160lm

Beam

70° (F)

Photometrics



$\alpha = 70^\circ$



Finishes

- UV Textured Black
- UV Textured White
- Anodised Aluminium

LED

- Colour Temp | 3000K
- CRI | 80+
- Efficacy | Up to 36lm/w
- Colour Deviation | SDCM \leq 3
- Lifetime | 64,000h L70

General Specifications

- Material | Powder Coated Aluminium
- IP | 65
- Warranty | 3 Years

Driver

- Power Factor | >0.90
- 240V Built-in Non-Dimmable Driver



A	B	C	D	E	F	A	B	C	D	E	F
MINQ	0004	TB	30	F	-	MINQ	0004	TB	30	F	-
Example: MINQ0004.TB30.F						Driver (DALI) drivers can be configured via Product Toolbox					
Refer to data sheet for available configurations.						Standard Non-Dimmable Driver included					
Visit Product Toolbox at unios.com/minq to configure compatible Osram/Tridonic DALI drivers.											

WALL SURFACE

