





Vega

Surface Light

The reliable and resilient outdoor luminaire for ultimate utility



Open Face	Eyelid
Measurements (mm)	Measurements (mm)
	
Absolute Luminous Flux	Absolute Luminous Flux
14W (450mA) 990lm (at 3000K) 1140lm (at 4000K)	12W (300mA) 670lm (at 3000K) 800lm (at 4000K)
Beam	Beam
110° (F)	115° (F)

Finishes

UV Textured Black

UV Textured White

General Specifications

Material	UV Powder Coated Toughened Polycarbonate
IP	65
Impact Rating	IK10
Warranty	3 Years

LED

Colour Temp	3000K, 4000K
CRI (Ra/R9)	80+ / >0
Efficacy	Up to 81lm/W
Colour Deviation	SDCM ≤ 3
Lifetime	>54,000h L70B10

Driver

240V Built-in Non-Dimmable Driver

240V Remote Tridonic one4all DALI Driver (TD)

240V Remote Tridonic basicDIM Bluetooth Driver (TB)




Available in an open face or eyelid variation

IK10 rating makes the Vega impact resistant and ideal for public applications


Designed with vandal resistant screws

Can be used in ceiling or wall applications

Beam Options



Flood (Open Face)
110° (F)



Flood (Eyelid)
115° (F)