



Above: Multi-residential application
Left: Vega Eyelid model







Vega




OUTDOOR LIGHT

The Vega Outdoor Light has been rigorously tested to be resistant to discolouring or corrosion. Whether wall or ceiling mounted, this outdoor luminaire will perform in any outdoor environment. This luminaire is integrated with four hex screws for improved vandal proof capabilities.

- New Vega Eyelid design suitable for all outdoor applications
- UV treated diffuser prevents cracking and discolouration
- A versatile luminaire that delivers maximum light output in a durable body

Open Face		
Measurements (mm)		
		
Ø 270	90	
Absolute Luminous Flux		
	3000K	4000K
14W (450mA)	990lm	1140lm
Beam		
110° (F)		


Eyelid		
Measurements (mm)		
		
Ø 270	90	
Absolute Luminous Flux		
	3000K	4000K
12W (300mA)	670lm	800lm
Beam		
110° (F)		

Finishes	
UV Textured Black	
UV Textured White	
UV Textured Silver	

Driver	
Power Factor	>0.90
240V Built-in Non-Dimmable Driver	
Dimming DALI Dim Optional	

General Specifications	
Material	UV Powder Coated Toughened Polycarbonate
IP	65
IK	10
Warranty	3 Years
LED	
Colour Temp	3000K, 4000K
CRI	80+
Efficiency	Up to 81lm/w
Colour Deviation	SDCM≤3
Lifetime	70,000h L70

Notes	
DALI Driver must be remote.	



A	B	C	D	E	F
VEGA	0012	TB	30	F	- Driver
Example: VEGA0012.TB30.F					
Refer to data sheet for available configurations.					
Visit Product Toolbox at unios.com/vega to configure compatible Osram/Tridonic DALI drivers.					
Product Family					
VEGA Vega Open Face Outdoor Light					
VEGE Vega Eyelid Outdoor Light					
Power					
0012 12W					
0014 14W					
Finish					
TB Textured Black					
TW Textured White					
TS Textured Silver					
Beam					
F Flood					
CCT					
30 3000K					
40 4000K					
Driver					
Standard Non-Dimmable Driver included					

