

Titanium 260mm Surface Mounted Starlight

TIST0043.TB40.W-TSSM0260.TB

Absolute Luminous Flux 5W (150mA) / 476lm Beam 50° (W)



Product Type	Surface Mounted
Diameter	Ø46mm
Height	260mm
Finish	Textured Black
Colour Temp	4000K
Class	Class I
Beam Angle	50° (W)
Material	Powder Coated Aluminium
IP Rating	IP20
UGR	<13
Warranty	5 Years
CRI	92+ (R9: >50)
Efficacy	Up to 82lm/W
Colour Deviation	SDCM ≤ 2
Lifetime	>55,000h L80B10

Electronic Control Gear

Built-in UNIOS PC Driver
STD-IPC

Dimensions: Var.


Downloads

General Specifications	
Product Images	
IES Files	
Installation Instructions	
Revit Family	
Sketchup Objects	
ArchCAD Library	

Features

- Establishing new heights and shifting cord lengths, these minimal canisters offer complete design flexibility.
- The design and engineering behind the Titanium Starlight is aimed at providing optimum visual comfort.
- The super low-glare design blocks the light source from direct line of sight, creating a soft and comfortable spread of light.
- Multiple versions of the Titanium Starlight in surface mounted or suspended options ensures various applications can be created from this one luminaire family.

Light Distribution



Luminaire Notes

For Casambi Bluetooth options, please refer to unios.com/smartcontrols
For any custom requests, please specify in the notes section.

Ordering Code

Stocked Configuration (subject to availability) ●

TIST	0043	TB	40	W	-	TSSM0260.TB		-	
PRODUCT	DIAMETER	FINISH	COLOUR TEMP	BEAM		ACCESSORIES			CONTROL GEAR

Contact Information

Name _____ Email _____
Company _____ Phone _____



[VIEW PRODUCT ONLINE](#)